

STREET FIGHTER PLUS+™

The Street Fighter Plus+™ means a great value optic lens with tightened module spacing to increased lumen output, PLUS constant current!



SPECIFICATIONS

Beam Angle	160° Low Dome, Batwing Optic
Certifications	UL & cUL Recognized (SAM Manual), CE, RoHs
Dimensions	0.6"W x 3.25"L x 0.3"H
Efficacy	See Product Options
Fastening	Peel & stick / Mechanical screw hole
Input	12VDC
Intensity	See Product Options
Max Mods (Series)	22 ft (40 mods)
Operating Temp	-40° to +60°C
Packaging	44 ft (80 mods) per bag or 528 ft (960 mods) per case
Power	0.72W/mod (1.3W/ft)
Power Supply	P-LED 12VDC
Protection Grade	IP67
Run Footage	44 ft (80 mods)/60W PS
Spacing	1.8 mods/ft (fully stretched)
Warranty	5 Year Product / 5 Year Limited Labor

FEATURES

- Great in areas with indirect water exposure or salt spray
- Split wires for easy module adjustment and splicing
- LM-79/LM-80 third party tested
- VHB tape coupled with a mechanical screw-hole mounting option

WIRING DETAILS

White/Red	Positive
White/Black	Negative

PRODUCT OPTIONS

Color	CCT	Efficacy	Intensity	Part Number
Warm White	3500K	100 LM/W	72 LM/mod (129.6 LM/ft)	PL-OP2-SF3-P-WW-CC*
Natural White	5000K	100 LM/W	72 LM/mod (129.6 LM/ft)	PL-OP2-SF3-P-NW-CC*
True White	7000K	100 LM/W	72 LM/mod (129.6 LM/ft)	PL-OP2-SF3-P-TW-CC*
Cool White	9000K	100 LM/W	72 LM/mod (129.6 LM/ft)	PL-OP2-SF3-P-CW-CC*

*CC represents constant current.

RECOMMENDED COVERAGE CHART

Depth*	Max. Stroke	Row Spacing
	Single Row	Multi-Rows O.C.
4"	9"	5"
5"	12"	10"
6"	14"	12"
7"	14"	12"

Note: Product and depth may vary depending on face material and desired brightness.

