





PosterBOX 3 engineered specifically for large, fabric-faced light box applications, is the bright and uniform lighting solution this unique application requires. One of the brightest modules on the market, PosterBOX 3 delivers beautiful, smooth illumination in light boxes up to 3 m (10 ft) in height, and with an output of 1700 lumens (Long) and built-in LED module spacers, striping and spotting are a thing of the past.

- Uniform illumination in large cabinets with depths as shallow as 75 mm (3") for single-sided applications, 100 mm (4") for double-sided applications, and up to 3 m (10 ft) in height
- High efficiency and long life
- Built-in module spacer eliminates measuring, yielding perfect results every time
- Also great for wall wash applications when used in conjunction with a suitable extrusion



PosterBOX ID is a value-driven lighting solution delivering the power and brilliance of PosterBOX 3 to indoor applications — trimming unnecessary hardware and outdoor protection to offer a low-cost solution with the same quality and reliability you've come to expect from SloanLED.


- Illuminate box widths up to 3 m (10 ft) by placing product on opposing sides of the display
- Top-tier LED chips and high-performance optics
- Brightest in class
- Constant Current Technology
- 10-year parts and labor assistance warranty

For more information on our Sign Cabinet/Box collection of products, visit SloanLED.com.

We've got you covered.


At SloanLED, our goal is more than just selling quality, reliable lighting products. We anticipate our customer's needs and deliver comprehensive solutions for a smooth, positive experience.

While most commercial LED light manufacturers offer 5-year limited warranties, SloanLED offers a 10-year limited product and labor warranty. Additionally, PosterBOX ID is covered by a licensing agreement which protects both the installer and end-user from Signify (Philips Lighting) royalty fees associated with the patented side-lighting of poster boxes, signs, and retail displays so you can have confidence for the road ahead, knowing your investment in signage is well-protected!



Dimensions





PosterBOX ID Short

PosterBOX 3

Large, shallow fabric-faced light box illumination

Specifications

Part number	Short 701946-6WSRP1		
	Long 701946-6WLRP1		
LEDs per assembly	Short 3		
	Long 6		
Min. cabinet depth	.Single-sided 75 mm (3 in)		
	Double-sided 100 mm (4 in)		
Viewing angle	$12.2^{\circ} \times 44.8^{\circ}$ illumination		
Operating temperature	40°C to +70°C (-40°F to +158°F)		
Protection class	IP66		
Life rating	>60,000 hours		
Power per module	Short 7.2 W		
	Long 14.0 W		
Optional dimming	PWM (Pulse width modulation,		
	SloanLED Universal LED Wireless Dimmer 601115)		
Efficacy	Short 118 lm/W		
	<i>Long</i> 121 lm/W		
Power capacity	Per SloanLED 100 W 24 VDC power supply*		
	Short 12 units		
	Long 6 units		
Fastening	Mechanical fasteners, Peel-n-stick (optional)		
Packaging	Six (6) assemblies per tray, 5 trays per carton		
Color temperature	6500 K		
Lumens per assembly	Short 850		
	Long 1,700		

PosterBOX ID

High-performance light box illumination for interior signage and POP applications

Specifications

Part number	Short	701946-6WSNP1	
	Long	701946-6WLNP1	
LEDs per assembly	Short	3	
	Long	6	
Min. cabinet depth	Single-sided	75 mm (3 in)	
	Double-sided	100 mm (4 in)	
Viewing angle	15° x 45° illumination	ı	
Operating temperature	40°C to +40°C (-40	°F to +104°F)	
Location rating	Indoor use only		
Life rating	>60,000 hours		
Power per assembly	Short	7.2 W	
	Long	14.0 W	
Optional dimming	PWM (Pulse width modulation,		
	SloanLED Universal LI	ED Wireless Dimmer 601115)	
Efficacy	Short	118 lm/W	
	Long	121 lm/W	
Power capacity	Per SloanLED 100 W 24 VDC power supply		
		Maximum of 12 units	
	Long	Maximum of 6 units	
Fastening	Peel-n-stick and mechanical		
Packaging	Six (6) assemblies per bag, 5 bags per carton		
Color temperature	6500 K		
Lumens per assembly	Short	850	
	Long	1,700	

Power Supply Capacity

	Max. units per	r power supply
24 VDC power supply	PosterBOX 3 & PosterBOX ID Short	PosterBOX 3 & PosterBOX ID Long
30 W Power Supply (EU/ROW ONLY)	3	1
60 W Power Supply	7	3
96 W Power Supply	12	6
3 x 96 W Power Supply	3×12	3×6
100 W Power Supply	12	6
150 W Power Supply (EU/ROW ONLY)	18	9
Power used per unit in Watts	7.2 W	14.0 W

^{*} Combination of units must not exceed maximum power supply output.

The SloanLED PosterBOX" product family is licensed by Signify (formally Philips Lighting) in relation to the following patents: North America: US7841733. Europe: EP1938298, NL1030161, NL2000273, DE202006020673.6. Asia: CN101300616. PosterBOX products are licensed under Signify's EnabLED program when bought as a PosterBOX lighting kit solution including a SloanLED power supply. Final application in which PosterBOX lighting kit solution is installed is covered by SloanLED's licensing agreement with Signify and free from any further royalties relating to the patents listed above.









SloanLED Headquarters

5725 Olivas Park Drive, Ventura, CA, USA 805.676.3200 • info@SloanLED.com















Argonstraat 110, 2718 SN Zoetermeer, NL +31 88 12 44 900 • europe@SloanLED.com